




FAKRO EN	LWF 60 (3s)	-	LXL-PVC	-











Ceiling structure in accordance with the fire classification

79-Fire-rated hatch
80-Tread
86-Hinge
88-Side bracket
90-LXH handrail
93-LXS stile end
94-Stringer (ladder side element)
686-Finishing lining slats LXL-PVC FAKRO
700-Concrete ceiling
714-Fire-resistant sealant
715-Insulation:rock wool with a min.density of 60kg/m^3
716-Spacing washer
718-Nail dowel mini. Ø 6x80


P Hatch board movement after opening	**S** Tread width	**E** Tread length
[cm]	[cm]	[cm]
5	8	34

LWF 60 - Loft ladder dimensions

H Room height	**H** Min. Room height	**A** Width ceiling opening dimensions	**B** Length ceiling opening dimensions	**K** Folded loft ladder height	**R** Swing space	**C** Distance after ladder unfolding	**T** Box height	**WxL** Outside box dimensions	**MxN** Inside box dimensions	**G** Distance between treads
[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]
280	234	60	120	38	164	129	22,5	58x118	54x114	25
		70	120					68x118	64x114	
		70	130					68x128	64x124	
		70	140					68x138	64x134	
		86	130					84x128	80x124	
305	242	70	130		178	139		68x128	64x124	
		70	140					68x138	64x134	
		86	130					84x128	80x124	

FAKRO

LWF 60 (3s)



Technical drawing:
The LWF 60 (4-section version) Loft Ladder
CONCRETE CEILING

FORMAT:	SCALE:	DATE:
A4	1:20/1:10	03.2026

Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.