

1. Unique identification code of the product-type: **FTP-V U41, FTU-V U41, FTW-V U41  
FTP-X U41, FTU-X U41, FTW-X U41**
2. Intended use/es: **Wooden roof windows intended to be used in domestic and commercial location.**
3. Manufacturer: **FAKRO PP Sp. z o.o.  
ul. Węgierska 144a,  
33-300 Nowy Sącz, Poland  
fakro@fakro.pl**
4. Authorised representative: **./.**
5. System/s of AVCP: **3**
6. Harmonised standard: **EN 14351-1:2006+A2:2016**  
 Notified body/ies: **Mendelova univerzita v Brně (1389)**

**7. Declared performance/s:**

Essential characteristics	Performance		Harmonised technical specification
	FTP-V U41 FTU-V U41 FTW-V U41	FTP-X U41 FTU-X U41 FTW-X U41	
7.1 Resistance to wind load	Class C4/B4 (1)	Class C4/B4 (1)	EN 14351-1:2006+A2:2016
7.2 Resistance to snow and permanent load	4H-16-4-16-4 (2)	4H-16-4-16-4 (2)	
7.3 Reaction to fire	npd (3)	npd (3)	
7.4 External fire performance	npd	npd	
7.5 Watertightness. Non-shielded (A)	Class 9A	Class 9A	
7.6 Impact resistance	Class 3 - 450mm	Class 3 - 450mm	
7.7 Load-bearing capacity of safety device	Threshold value (350 N)	Threshold value (350 N)	
7.8 Acoustic performance	36 (-2,-6) [dB]	36 (-2;-7) [dB]	
7.9 Thermal transmittance	1.1 [W/m <sup>2</sup> K] (4)	1.1 [W/m <sup>2</sup> K] (4)	
Radiation properties:			
7.10 - Solar factor g	0.42	0.42	
- Light transmittance	0.64	0.64	
7.11 Air permeability	Class 4	Class 4	

(1) for the windows with the width of > 114 cm and height of >140 cm: npd, (2) H – external pane toughened, (3) npd – no performance determined, (4) for the reference size (1,14 x 1,40) m – test according to standard EN ISO 12567-2

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Ewa Łukaszczyk-Haslik

Nowy Sącz, 04/12/2023

