

	Declaration of Performance	No. 09NWP50/CPR/14351/24
---	-----------------------------------	---

1. Unique identification code of the product-type: **FXP P50, FXU P50, FXW P50**
2. Intended use/es: **Wooden roof windows intended to be used in domestic and commercial location.**
3. Manufacturer: **FAKRO PP Sp. z o.o.
ul. Węgierska 144a,
33-300 Nowy Sącz, Poland
fakro@fakro.pl**
4. Authorised representative: **./.**
5. System/s of AVCP: **3**
6. Harmonised standard: **EN 14351-1:2006+A2:2016**
Notified body/ies: **Mobilne Laboratorium Techniki Budowlanej Sp. z o.o. (2189)
Politechnika Krakowska (2919)**

7. Declared performance/s:

Essential characteristics		Performance	Harmonised technical specification
		FXP P50 FXU P50 FXW P50	
7.1	Resistance to wind load	Class C5 (1)	EN 14351-1:2006+A2:2016
7.2	Resistance to snow and permanent load	4H-15-4-15-33.2 (2)	
7.3	Reaction to fire	npd (3)	
7.4	External fire performance	npd	
7.5	Watertightness. Non-shielded (A)	Class 9A	
7.6	Impact resistance	npd	
7.7	Load-bearing capacity of safety device	npd	
7.8	Acoustic performance	37 (-1,-2) dB	
7.9	Thermal transmittance	1.0 [W/m ² K] (4)	
7.10	Radiation properties:		
	- Solar factor g	0.42	
	- Light transmittance	0.63	
7.11	Air permeability	Class 4	

(1) for the windows with the width of > 114 cm and height of > 140 cm: npd, (2) H – external pane toughened, (3) npd – no performance determined (4) for the reference size (1,14 x 1,40) m – test according to standard EN ISO 12567-2

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Ewa Łukaszczyk-Haslik

Nowy Sącz, 25/11/2024

