

1. Unique identification code of the product-type: **PXP P50**
2. Intended use/es: **PVC roof windows intended to be used as communication in domestic and commercial locations.**
3. Manufacturer: **FAKRO PP Sp. z o.o.
ul. Węgierska 144a,
33-300 Nowy Sącz, Poland
fakro@fakro.pl**
4. Authorised representative: *./.*
5. System/s of AVCP: **3**
6. Harmonised standard: **EN 14351-1:2006+A2:2016**
Notified body/ies: **Mobilne Laboratorium Techniki Budowlanej (2189)
Politechnika Krakowska (2919)**

7. Declared performance/s:

| Essential characteristics | Performance | | Harmonised technical specification |
|--|------------------------------|--|------------------------------------|
| | PXP P50 | | |
| 7.1 Resistance to wind load | Class C4 (1) | | EN 14351-1:2006+A2:2016 |
| 7.2 Resistance to snow and permanent load | 4H-15-4-15-33.2 (2) | | |
| 7.3 Reaction to fire | npd (3) | | |
| 7.4 External fire performance | npd | | |
| 7.5 Watertightness. Non-shielded (A) | Class 9A | | |
| 7.6 Impact resistance | npd | | |
| 7.7 Load-bearing capacity of safety device | npd | | |
| 7.8 Acoustic performance | npd | | |
| 7.9 Thermal transmittance | 1.0 [W/m ² K] (4) | | |
| 7.10 Radiation properties: | | | |
| - Solar factor g | 0.42 | | |
| - Light transmittance | 0.63 | | |
| 7.11 Air permeability | Class 4 | | |

(1) for the windows with the width of > 114 cm and height of >140 cm: npd, (2) H – external pane toughened, (3) npd – no performance determined, (4) for the reference size (1,14 x 1,40) m – test according to standard EN ISO 12567-2

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Ewa Łukaszczyk-Haslik

Nowy Sącz, 01/09/2025

