

1. Unique identification code of the product-type: **FOP-V P50 FOR P50, FOP-V P50 FOL P50, FOP-V P50 FOX P50
FOP-X P50 FOR P50, FOP-X P50 FOL P50, FOP-X P50 FOX P50**
2. Intended use/es: **Wooden roof windows intended to be used in domestic and commercial location.**
3. Manufacturer: **FAKRO PP Sp. z o.o.
ul. Węgierska 144a,
33-300 Nowy Sącz, Poland
fakro@fakro.pl**
4. Authorised representative: *./.*
5. System/s of AVCP: **3**
6. Harmonised standard: **EN 14351-1:2006+A2:2016**
 Notified body/ies: **Mobilne Laboratorium Techniki Budowlanej (2189)
Instytut Techniki Budowlanej (1488)**

7. Declared performance/s:

Essential characteristics	Performance		Harmonised technical specification
	FOP-V P50 FOR/FOL/FOX P50	FOP-X P50 FOR/FOL/FOX P50	
7.1 Resistance to wind load	Class C3		EN 14351-1:2006+A2:2016
7.2 Resistance to snow and permanent load	4H-15-4-15-33.2 (1)		
7.3 Reaction to fire	npd (2)		
7.4 External fire performance	npd		
7.5 Watertightness. Non-shielded (A)	Class 9A		
7.6 Impact resistance	npd		
7.7 Load-bearing capacity of safety device	npd		
7.8 Acoustic performance	npd		
7.9 Thermal transmittance	1.1 [W/m ² K] (3)		
Radiation properties:			
7.10 - Solar factor g	0.42		
- Light transmittance	0.63		
7.11 Air permeability	Class 3		

(1) H – external pane toughened, (2) npd – no performance determined, (3) calculation according to standard PN-EN ISO 10077-1, p. 6

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Ewa Łukaszczyk-Haslik

Nowy Sącz, 10/03/2025

