

1. Unique identification code of the product- **FWP P50, FWU P50, FWW P50**
type:
2. Intended use/es: **Wooden side hung escape window intended to be used in domestic and commercial location**
3. Manufacturer: **FAKRO PP Sp. z o.o.
ul. Węgierska 144a,
33-300 Nowy Sącz, Poland
fakro@fakro.pl**
4. Authorised representative: **not applicable**
5. System/s of AVCP: **3**
6. Harmonised standard: **EN 14351-1:2006+A2:2016**
Notified body/ies: **Laboratorium Techniki Budowlanej (1827)
Mobilne Laboratorium Techniki Budowlanej (2189)
Politechnika Krakowska (2919)**
7. Declared performance/s:

Essential characteristics		Performance		Harmonised technical specification
		FWP P50	FWU P50	
7.1	Resistance to wind load	Class C4 (1)		EN 14351-1:2006+A2:2016
7.2	Resistance to snow and permanent load	4H-15-4-15-33.2 (2)		
7.3	Reaction to fire	npd (3)		
7.4	External fire performance	npd		
7.5	Watertightness. Non-shielded (A)	Class E900		
7.6	Impact resistance	Class 3 - 450mm		
7.7	Load-bearing capacity of safety device	npd		
7.8	Acoustic performance	38 (-1,-3) [dB]		
7.9	Thermal transmittance	1.1 [W/m ² K] (4)		
7.10	Radiation properties: - Solar factor g - Light transmittance	0.42 .063		
7.11	Air permeability	Class 4		

(1) for the windows with the width of > 114 cm and height of >140 cm: npd, (2) H – external pane toughened, (3) npd – no performance determined, (4) for the reference size (1,14 x 1,40) m – test according to standard EN ISO 12567-2

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Ewa Łukaszczyk-Haslik

Nowy Sącz, 25/11/2024

