

1. Unique identification code of the product- **PWP U41**  
type:
2. Intended use/es: **Plastic side hung escape window intended to be used in domestic and commercial location**
3. Manufacturer: **FAKRO PP Sp. z o.o.  
ul. Węgierska 144a,  
33-300 Nowy Sącz, Poland  
fakro@fakro.pl**
4. Authorised representative: **not applicable**
5. System/s of AVCP: **3**
6. Harmonised standard: **EN 14351-1:2006+A2:2016**  
Notified body/ies: **Laboratorium Techniki Budowlanej (1827)  
Mobilne Laboratorium Techniki Budowlanej (2189)  
Politechnika Krakowska (2919)**

**7. Declared performance/s:**

Essential characteristics		Performance	Harmonised technical specification
		PWP U41	
7.1	Resistance to wind load	Class C4 (1)	EN 14351-1:2006+A2:2016
7.2	Resistance to snow and permanent load	4H-16-4-16-4 (2)	
7.3	Reaction to fire	npd (3)	
7.4	External fire performance	npd	
7.5	Watertightness. Non-shielded (A)	Class E900	
7.6	Impact resistance	Class 3 - 450mm	
7.7	Load-bearing capacity of safety device	npd	
7.8	Acoustic performance	35 (-1, -4) [dB]	
7.9	Thermal transmittance	1.1 [W/m <sup>2</sup> K] (4)	
7.10	Radiation properties:		
	- Solar factor g	0.42	
	- Light transmittance	0.64	
7.11	Air permeability	Class 3	

(1) for the windows with the width of > 94 cm and height of >140 cm: npd, (2) H – external pane toughened, (3) npd – no performance determined, (4) for the reference size (1,14 x 1,40) m – test according to standard EN ISO 12567-2

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Ewa Łukaszczyk-Haslik

Nowy Sącz, 25/11/2024

